

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended) ~~A~~Method of signal processing for a spread spectrum digital radio communication receiver, comprising the ~~5~~-following steps:

~~determine~~determining a propagation profile of a propagation channel between sending means and the receiver, including at least one propagation path associated with a reception energy;

~~measure~~measuring data relating to an energy distribution in the propagation profile;

~~estimate~~estimating information symbols carried by a signal ~~received~~-originating from said sending means ~~of sending and received~~ over the propagation channel, by applying to said signal a processing taking into account a predetermined maximum number of propagation paths, said propagation paths taken into account being chosen according to a criterion selected from several criteria,

in which said criterion is selected as a function of the measured data relating to the energy distribution in the propagation profile.

2. (currently amended) ~~A~~Method according to Claim 1, in which the step of determining a propagation profile of a propagation channel between the sending means and the receiver comprises a processing applied to the signal received identifying, on the basis of an analysis of an impulse response of the propagation channel between the sending means and the

receiver, a number of propagation paths detected and respective reception energies for these paths.

3. (currently amended) A ~~M~~method according to Claim 1, in which said propagation paths taken into account are chosen according to a criterion selected from a set comprising a first criterion according to which the predetermined maximum number of propagation paths of greatest energy on average are taken into account, and a second criterion according to which the predetermined maximum number of propagation paths of largest instantaneous energy are taken into account.

4. (currently amended) A ~~M~~method according to Claim 1, in which the measured data relating to the energy distribution in the propagation profile comprise a measurement of energy dispersion for the propagation paths detected.

5. (currently amended) A ~~M~~method according to Claim 4, in which the selection of said criterion as a function of the measured data relating to the energy distribution in the propagation profile comprises a comparison of said measurement of energy dispersion for the propagation paths detected with a threshold.

6. (currently amended) A ~~M~~method according to Claim 5, in which said threshold is obtained in relation to a prior choice of a gap in performance between two strategies for choosing propagation paths taken into account in said processing according to respective criteria.

7. (currently amended) A Method according to Claim 6, in which the obtaining of the threshold is done on the basis of correspondences between an energy dispersion in a propagation profile and a gap in performance between two strategies for choosing propagation paths according to respective criteria, the correspondences being preestablished under various radio conditions.

8. (currently amended) A Method according to Claim 4, in which the measurement of energy dispersion for the propagation paths detected comprises an estimation of a mean energy gap between the propagation paths detected.

9. (currently amended) A Method according to Claim 8, in which the mean energy gap between the propagation paths detected is estimated in the least squares sense.

10. (currently amended) A Method according to Claim 8, in which the mean energy gap between the propagation paths detected is estimated according to an arithmetic mean of ratios between the energies of consecutive paths from among the propagation paths detected.

11. (currently amended) A Spread spectrum digital radio communication receiver comprising means for determining a propagation profile of a propagation channel between sending means and the receiver, including at least one propagation path associated with a reception energy, means for measuring data relating to an energy distribution in the propagation

profile, means for choosing a predetermined maximum number of propagation paths according to a criterion for choosing, means for estimating information symbols carried by a signal received-originating from said sending means of sending and received over the propagation channel, by applying to said signal a processing taking into account the paths chosen, said spread spectrum digital radio communication receiver furthermore comprising means for selecting a said criterion for choosing from several criteria, designed to select a said criterion for choosing being selected as a function of the data measured by the means relating to the energy distribution in the propagation profile.

12. (currently amended) A Rreceiver according to Claim 11, in which the means for determining a propagation profile of a propagation channel between sending means and the receiver comprise means for applying to the signal received a processing identifying, on the basis of an analysis of an impulse response of the propagation channel between the sending means and the receiver, a number of propagation paths detected and respective reception energies for these paths.

13. (currently amended) A Rreceiver according to Claim 11, in which the means for selecting a criterion for choosing from several criteria as a function of the measured data relating to the energy distribution in the propagation profile are designed to select a criterion for choosing from a set comprising a first criterion according to which the predetermined maximum number of propagation paths of greatest energy on average are taken into account, and a second criterion

according to which the predetermined maximum number of propagation paths of largest instantaneous energy are taken into account.

14. (currently amended) A ~~R~~receiver according to Claim 11, in which the means for measuring data relating to an energy distribution in the propagation profile comprise means for measuring an energy dispersion for the propagation paths detected.

15. (currently amended) A ~~R~~receiver according to Claim 14, in which the means for selecting a criterion for choosing from several criteria as a function of the measured data relating to the energy distribution in the propagation profile are designed to make a selection which comprises a comparison of said measurement of energy dispersion for the propagation paths detected with a threshold.

16. (currently amended) A ~~R~~receiver according to Claim 15, in which the means for selecting a criterion for choosing from several criteria as a function of the measured data relating to the energy distribution in the propagation profile are designed to obtain said threshold in relation to a prior choice of a gap in performance between two strategies for choosing the propagation paths.

17. (currently amended) A ~~R~~receiver according to Claim 16, in which the means for selecting a criterion for choosing from several criteria as a function of the measured data relating to the energy distribution in the propagation profile comprise means for storing correspondences

between an energy dispersion in a propagation profile and a gap in performance between two strategies for choosing propagation paths according to respective criteria, said correspondences being preestablished under various radio conditions.

18. (currently amended) A ~~R~~receiver according to Claim 17, in which the means for selecting a criterion for choosing from several criteria as a function of the measured data relating to the energy distribution in the propagation profile are designed to obtain the threshold on the basis of the correspondences stored in the means 44A-~~t~~ for storing correspondences between an energy dispersion in a propagation profile and a gap in performance between two strategies for choosing the propagation paths according to respective criteria.

19. (currently amended) A ~~R~~receiver according to Claim 14, in which the means for measuring an energy dispersion for the propagation paths detected are designed to estimate a mean energy gap between the propagation paths detected.

20. (currently amended) A ~~R~~receiver according to Claim 19, in which the means for measuring an energy dispersion for the propagation paths detected are designed to estimate a mean energy gap between the propagation paths detected in the least squares sense.

21. (currently amended) A ~~R~~receiver according to Claim 19, in which the means for measuring an energy dispersion for the propagation paths detected are designed to estimate a

mean energy gap between the propagation paths detected according to an arithmetic mean of ratios between the energies of consecutive paths from among the propagation paths detected.

22. (currently amended) ~~A~~ Ccomputer ~~programme~~program stored on a tangible medium, loadable into a memory associated with a processor, and comprising instructions for the implementation, during the execution of said ~~programme~~program by ~~the~~a processor, of the followings steps :

~~determine~~determining a propagation profile of a propagation channel between sending means and the receiver, including at least one propagation path associated with a reception energy;

~~measure~~measuring data relating to an energy distribution in the propagation profile;  
~~estimate~~estimating information symbols carried by a signal ~~received~~ originating from said sending means ~~of sending~~ and received over the propagation channel, by applying to the said signal a processing taking into account a predetermined maximum number of propagation paths, the said propagation paths taken into account being chosen according to a criterion selected from several criteria,

in which said criterion is selected as a function of the measured data relating to the energy distribution ~~20~~ in the propagation profile.

23. (currently amended) ~~A~~ Ccomputer ~~programme~~program according to claim 22, in which the step of determining a propagation profile of a propagation channel between sending means and the receiver comprises a processing applied to the signal received identifying, on the

basis of an analysis of an impulse response of the propagation channel between the sending means and the receiver, a number of propagation paths detected and respective reception energies for these paths.

24. (currently amended) A ~~computer programme~~ program according to claim 22, in which said propagation paths taken into account are chosen according to a criterion selected from a set comprising a first criterion according to which the predetermined maximum number of propagation paths of greatest energy on average are taken into account, and a second criterion according to which the predetermined maximum number of propagation paths of largest instantaneous energy are taken into account.

25. (currently amended) A ~~computer programme~~ program according to claim 22, in which the measured data relating to the energy distribution in the propagation profile comprise a measurement of energy dispersion for the propagation paths detected.

26. (currently amended) A ~~computer programme~~ program according to claim 25, in which the selection of said criterion as a function of the measured data relating to the energy distribution in the propagation profile comprises a comparison of said measurement of energy dispersion for the propagation paths detected with a threshold.

27. (currently amended) A ~~computer programme~~ program according to claim 26, in which said threshold is obtained in relation to a prior choice of a gap in performance between



two strategies for choosing propagation paths taken into account in said processing according to respective criteria.

28. (currently amended) A computer program according to claim 27, in which the obtaining of the threshold is done on the basis of correspondences between an energy dispersion in a propagation profile and a gap in performance between two strategies for choosing propagation paths according to respective criteria, the correspondences being preestablished under various radio conditions.

29. (currently amended) A computer program according to claim 25, in which the measurement of energy dispersion for the propagation paths detected comprises an estimation of a mean energy gap between the propagation paths detected.

30. (currently amended) A computer program according to claim 29, in which the mean energy gap between the propagation paths detected is estimated in the least squares sense.

31. (currently amended) A computer program according to claim 29, in which the mean energy gap between the propagation paths detected is estimated according to an arithmetic mean of ratios between the energies of consecutive paths from among the propagation paths detected.

32. (currently amended) ~~A~~Ccomputer medium in which is recorded a ~~programme~~program comprising instructions for the implementation of the followings steps, when executed by a processor :

~~determine~~determining a propagation profile of a propagation channel between sending means and the receiver, including at least one propagation path associated with a reception energy;

~~measure~~measuring data relating to an energy distribution in the propagation profile;  
~~estimate~~estimating information symbols carried by a signal received originating from said sending means ~~of sending and received~~ over the propagation channel, by applying to the said signal a processing taking into account a predetermined maximum number of propagation paths, the said propagation paths taken into account being chosen according to a criterion selected from several criteria, said criterion being selected as a function of the measured data relating to the energy distribution in the propagation profile.